

# Technical Information

Current version 0  
18/03/2024

derypol

C/ Plató 6, Entlo. 5º- 08021 Barcelona (Spain)  
Tel. (93) 238 90 90, Fax (93) 238 90 91  
www.derypol.com

## FP195

Product for industrial use

### DESCRIPTION

Resin for the formulation of floor care products. Forms a glossy film. It does not contain metallic salts.

### CHARACTERISTICS

Type of product	: Styrene acrylic copolymer in aqueous emulsion.
Appearance	: White milky liquid
Ionic character	: Anionic
Density	: 1.04 – 1.06 g/cm <sup>3</sup>
pH	: 7 – 8
Viscosity	: < 140 cP
Percent Solids	: 39 – 41 %
MFFT	: 55°C
Shelf life	: We recommend not keeping the product for more than 12 months

*Note: The parameters indicated here are not necessarily the specifications of the product. These will be agreed with each customer and will be part of the contract that must be respected for each batch supplied.*

## APPLICATION

- Product for the formulation of glossy emulsions for the care and maintenance of floors.
- Recommended for both industrial and domestic floors.
- Consult our technical staff in case of any doubt.

## BENEFITS

- Glossy film formation of excellent quality.
- Excellent resistance to traffic and abrasion, washing with water and detergents.
- Good dirt repellency.
- Low residual ammoniacal odour.

## STORAGE AND DISTRIBUTION

- The product should be kept in a covered place, the container tightly closed, protected from sunlight and within the temperature range of 10 to 30 °C. Protect from frost. Check the Material Safety Data Sheet.
- After opening, avoid contamination. If the package is left open, water may evaporate from the product and cause the formation of skins and lumps.
- Normal hygiene and safety measures are recommended for the handling of any chemical product.
- There is a great variety of containers. Check with our Customer Service in order to choose the most convenient one.

## REGULATORY

Consult our technical staff in case of any doubt.