

Technical Information

Current version 0
19/01/2024

derypol

C/ Plató 6, Entlo. 5º- 08021 Barcelona (Spain)
Tel. (93) 238 90 90, Fax (93) 238 90 91
www.derypol.com

HIMOLOC DR2500GR

Product for water treatments

DESCRIPTION

Water treatment flocculant where a low cationic charge is needed.

Better dissolution compared to emulsion and solid products.

The product is free of organic solvents, surfactants and volatile organic compounds (VOCs).

Its main ingredients are: polymer, salts and water.

Product designed to be used in the treatment of effluents whose solid fraction can be reused in the manufacture of compounds for animal feed.

CHARACTERISTICS

Type of product	: Water dispersion cationic polymer
Appearance	: White milky liquid
Ionic character	: Low cationic
Odor	: Salty odor
Density	: 1.2 g/cm ³
Residual Acrylamide	: < 10 ppm
pH	: 3 – 4.1
Viscosity	: 25 – 400 cP
Molecular weight	: High
Shelf life	: We recommend not keeping the product for more than 9 months.

Note: The parameters indicated here are not necessarily the specifications of the product. These will be agreed with each customer and will be part of the contract that must be respected for each batch supplied.



APPLICATION

- It is recommended to dissolve the product in water prior to use. It dissolves easily in any proportion. The only limitation is the viscosity of the solution.
- It is advisable not to exceed concentrations higher than 5%.
- It can be dosed using a static mixer.
- Any quality of water can be used for its preparation. Depending on it, the final solution will have a variable stability or variable usage time.
- It can work alone or in combination with other products commonly used in water treatment, such as: aluminum sulphate, aluminum polychloride, ferric chloride, polyamine, lime, etc.
- In order to achieve the maximum product performance it is necessary to choose the most appropriate dosage and dosage point.
- It is important to avoid the entry of water into the product circuit, so it is recommended to use non-return valves. If this were to happen, gels could be formed and could block the pipes.
- If the stored product is submitted to significant cyclic temperature changes, gel particles may be generated on the surface as a result of water evaporation-condensation phenomena.
- The product packed in translucent containers can acquire yellowish tones due to the effect of sunlight. However, this does not affect the quality or performance of the product
- Consult our technical staff in case of any doubt.

BENEFITS

The following treatments are recommended:

- Flocculant used in industrial waters (decantation or flotation).
- Mining: Separation of minerals
- Water treatment: separation of oils and grease by flotation.
- Sludge treatment (dehydration in belt and press filters, centrifuge, screw press, etc ...).

It does not cause the emission of Volatile Organic Compounds (VOCs).

STORAGE AND DISTRIBUTION

- The product should be kept in a covered place, the container tightly closed, protected from sunlight and within the temperature range recommended in Section 7 of the Safety Data Sheet.
- Once the container is open, avoid contamination with any other water based product and/or with strong bases. Check the Material Safety Data Sheet.
- Take the habitual precautions when handling a chemical product. Avoid the product to contact with eyes, skin or clothes.
- There is a great variety of containers. Check with our Customer Service in order to choose the most convenient one.

REGULATORY

- Consult our technical staff in case of any doubt.
- GRAS certification available.