# **Technical Information**

Current revision 4.1 25/01/2023



C/ Plató 6, Entlo. 5º- 08021 Barcelona (Spain) Tel. (93) 238 90 90 Fax (93) 238 90 91 www.derypol.com

# Hyfloc FIC9900

#### **Product for water treatments**

## **DESCRIPTION**

Water and sludge treatment cross-linked flocculant where a high cationic charge is needed.

#### **CHARACTERISTICS**


Type of product : Emulsion cationic polymer Appearance : Whitish opaque liquid

Ionic character: High CationicOdor: HydrocarbonDensity: 1.04 g/m³Viscosity: 350 - 2000 cP

Molecular weight : High

Shelf life : We recommend not keeping the product for more than 6 months

Note: The parameters indicated here are not necessarily the specifications of the product. These will be agreed with each customer and will be part of the contract that must be respected for each batch supplied.



8/14/2019 EN (English) 1/2



#### **APPLICATION**

- It is recommended to dissolve the product in water prior to use. The only limitation is the viscosity of the solution.
- It is advisable to prepare around 0.5% and not to exceed concentrations higher than 1%.
- It can work alone or in combination with other products commonly used in water treatment, such as: aluminum sulphate, aluminum polychloride, ferric chloride, polyamine, lime, etc.
- Any quality of water can be used for its preparation. Depending on it, the final solution will have a variable stability or variable usage time.
- In order to achieve the maximum product performance it is necessary to choose the most appropriate dosage and dosage point.
- It is important to avoid the entry of water into the product circuit, so it is recommended to use non-return valves.
  If this were to happen, gels could be formed and could block the pipes.

Consult our technical staff in case of any doubt.

#### **BENEFITS**

The following treatments are recommended:

- Industrial Water Flocculant (decantation or flotation).
- Because of its cross-linked structure combined with a high molecular weight, this product is recommended for high speed centrifuges since it forms a very resistant floc and provides good dewatering rations.
- Effective in a wide range of pH.

#### STORAGE AND DISTRIBUTION

- The product should be kept in a covered place, the container tightly closed, protected from sunlight and within the temperature range recommended in Section 7 of the Safety Data Sheet.
- Once the container is open, avoid contamination. Check the Material Safety Data Sheet.
- Take the habitual precautions when handling a chemical product. Avoid the product to contact with eyes, skin
  or clothes.
- There is a great variety of containers. Check with our Customer Service in order to choose the most convenient one.

### **REGULATORY**

Consult our technical staff in case of any doubt.

8/14/2019 EN (English) 2/2