

# Technical Information

Current version 0  
04/02/2021

derypol

C/ Plató 6, Entlo. 5<sup>o</sup>- 08021 Barcelona (Spain)  
Tel. (93) 238 90 90, Fax (93) 238 90 91  
www.derypol.com

## Limos 70

Product for the closed circuits of water

### DESCRIPTION

Antifouling / Dispersant product for industrial use.

### CHARACTERISTICS

Appearance	: Transparent liquid or slightly opalescent
Density	: 1.2 – 1.3 g/cm <sup>3</sup>
pH	: 5 – 7
Viscosity	: < 100 cP
Shelf life	: We recommend not keeping the product more than 12 months

*Note: The parameters indicated here are not necessarily the specifications of the product. These will be agreed with each customer and will be part of the contract that must be respected for each batch supplied.*

### APPLICATION

- In order to achieve the maximum product performance it is necessary to choose the most appropriate dosage and dosage point. It depends on a variety of factors such as the concentration of encrusted salts or the quality of the water, but generally the recommended doses are from 1 to 10 ppm.

Consult our technical staff in case of any doubt.

### BENEFITS

- Corrosion inhibitor.
- It avoids the deposition of inorganic salts such as calcium sulfate, prolonging the life of the membranes in reverse osmosis processes.
- Compatible with all types of membranes.
- Compatible with compounds from the pre-treatment coagulation-flocculation processes.

## STORAGE AND DISTRIBUTION

- The product should be kept in a covered place, the container tightly closed, protected from sunlight and within the temperature range recommended in Section 7 of the Safety Data Sheet.
- Once the container is open, avoid contamination. Check the Material Safety Data Sheet.
- Take the habitual precautions when handling a chemical product. Avoid the product to contact with eyes, skin or clothes.
- There is a great variety of containers. Check with our Customer Service in order to choose the most convenient one.

## REGULATORY

Consult our technical staff in case of any doubt.